

# TABLE OF CONTENTS

<b>CHAPTER 1</b>	<b>Introduction.....</b>	<b>1</b>
1.1.	Background.....	3
1.1.1.	Token Bucket Mechanism .....	3
1.1.2.	The IEEE 802.11 Standard .....	4
1.1.3.	The IEEE 802.11e Standard.....	5
1.1.4.	The IEEE 802.16 Standard .....	9
1.2.	Motivation .....	13
1.3.	Organization .....	14
<b>CHAPTER 2</b>	<b>Related Work.....</b>	<b>15</b>
2.1.	Markov Chain Studies about 802.11e .....	15
2.2.	Token Bucket and Call Admission Control about 802.16.....	18
<b>CHAPTER 3</b>	<b>IEEE 802.11e EDCA Markov Chain Model.....</b>	<b>22</b>
3.1.	Model Assumption.....	23
3.2.	Model Introduction.....	23
3.3.	Markov Chain State .....	26
3.4.	Transition Probability Matrix .....	27
3.5.	Delay, Throughput and Packet Drop rate Calculation.....	33
3.6.	Model Validation .....	34
3.6.1.	802.11e MAC Delay.....	36

3.6.2.	802.11e Packet Drop rate & Throughput.....	38
<b>CHAPTER 4</b>	<b>Improvement Mechanism .....</b>	<b>40</b>
4.1.	Call Admission Control (CAC).....	40
4.1.1.	Delay requirement .....	40
4.1.2.	Bandwidth requirement .....	41
4.2.	Token Bucket Mechanism .....	42
4.2.1.	Token Bucket Parameters .....	42
4.2.2.	Token Rate and Bucket Size Initialize.....	44
4.2.3.	Token Rate and Bucket Size Tuning.....	44
4.3.	Packet Drop Mechanism.....	47
<b>CHAPTER 5</b>	<b>Simulation.....</b>	<b>48</b>
5.1.	Delay.....	49
5.2.	Packet Drop rate .....	51
5.3.	Throughput .....	53
<b>CHAPTER 6</b>	<b>Conclusions and Future Work.....</b>	<b>55</b>
<b>References</b>	<b>.....</b>	<b>56</b>

## LIST OF TABLES

Table 1-1: Default EDCA Parameter set. ....	7
Table 1-2: Four QoS classes of 802.16. ....	10
Table 3-1: System Parameters. ....	35
Table 3-2: TSPEC for VO and VI. ....	35
Table 4-1: The delay from Qualnet. ....	41
Table 4-2: The delay from Markov Chain.....	41
Table 4-3: Token Bucket Parameters.....	43

## LIST OF FIGURES

Figure 1-1: The architecture in 802.11e and 802.16 interworking network. ....	3
Figure 1-2: The token bucket mechanism. ....	4
Figure 1-3: The Basic Access Method. ....	5
Figure 1-4: Multiple EDCA backoff entities contention with RTS/CTS. ....	8
Figure 1-5: Access Categories in the IEEE 802.11e. ....	9
Figure 1-6: The operation process of 802.16. ....	10
Figure 1-7: The frame structure of 802.16. ....	12
Figure 2-1: The Modified DCF Markov Chain in Backoff Period. ....	16
Figure 2-2: The EDCA Markov Chain for VO. ....	17
Figure 2-3: IEEE 802.16 PMP operation process. ....	18
Figure 2-4: The amount of packets that should be transmitted according to their deadlines. ....	20
Figure 2-5: Sharing the $b_i$ packets from time interval $[t+2f, t+3f]$ at time intervals $[t+3f, t+4f]$ and $[t+4f, t+5f]$ . ....	20
Figure 3-1: The 802.11e EDCA Markov Chain. ....	25
Figure 3-2: The conception of the IFAT and PIAT. ....	27
Figure 3-3: The conception of the probability P, Q and Z. ....	29
Figure 3-4: Transmission Time for COLL, SMALL, and LARGE. ....	32
Figure 3-5: Scenario 1 – MAC Delay time ( $N_{VI}$ ). ....	36
Figure 3-6: Scenario 2 – MAC Delay time ( $N_{VO} : N_{VI} = 1 : 1$ ). ....	36

Figure 3-7: Enlarging – MAC Delay time ( $N_{VI}$ ) ( $N_{VO} : N_{VI} = 1 : 1$ ). .....	37
Figure 3-8: Packet Drop rate ( $N_{VI}$ ).....	38
Figure 3-9: Throughput ( $N_{VI}$ ).....	38
Figure 4-1: The CAC algorithm.....	42
Figure 4-2: Transmission Time for COLL, SMALL, and LARGE. ....	46
Figure 5-1: Scenario 1 – Delay time ( $N_{VI}$ ).....	49
Figure 5-2: Scenario 2 – Delay time ( $N_{VO} : N_{VI} = 1 : 1$ ).....	49
Figure 5-3: Enlarge – Delay ( $N_{VI}$ ) ( $N_{VO} : N_{VI} = 1 : 1$ ) .....	50
Figure 5-4: Scenario 1 – Packet drop rate ( $N_{VI}$ ) .....	51
Figure 5-5: Scenario 2 – Packet drop rate ( $N_{VO} : N_{VI} = 1 : 1$ ).....	51
Figure 5-6: Enlarge – Packet drop rate ( $N_{VI}$ ) ( $N_{VO} : N_{VI} = 1 : 1$ ).....	52
Figure 5-7: Scenario 1 – Throughput ( $N_{VI}$ ).....	53
Figure 5-8: Scenario 2 – Throughput ( $N_{VO} : N_{VI} = 1 : 1$ ).....	53
Figure 5-9: Enlarge – Throughput ( $N_{VI}$ ) ( $N_{VO} : N_{VI} = 1 : 1$ ).....	54